

## Safe distances from flammable materials

Safe distances from flammable materials (cm)	P-116 / P-216 PT-216 GL water tank connection; water tank 40l P-11620 RV	P-120 / P-220 PT-220 GL water tank connection; water tank 40l P-12025 RV	S-116 / S-216 ST-216 GL STY-216 GL water tank connection; water tank 40l	S-120 / S-220 ST-220 GL STY-220 GL water tank connection; water tank 40l	PS; SS; SY models
Distance to adjacent wall	<b>50</b>	<b>50</b>	<b>40</b>	<b>40</b>	<b>25</b>
Distance to back wall	<b>30</b>	<b>30</b>	<b>25</b>	<b>25</b>	<b>15</b>
Distance from stoves to ceiling	<b>125</b>	<b>125</b>	<b>120</b>	<b>120</b>	<b>124</b>
Distance from smoke flue to ceiling	<b>108</b>	<b>108</b>	<b>108</b>	<b>108</b>	<b>108</b>
Thickness of insulating barrier of the stove's base	<b>6</b>	<b>6</b>	<b>6</b>	<b>6</b>	<b>15</b>
Distance from metal door to front wall	<b>50</b>	<b>50</b>	<b>50</b>	<b>50</b>	<b>50</b>
Distance from glassdoor to front wall	<b>65</b>	<b>65</b>	<b>65</b>	<b>65</b>	<b>65</b>